



REX POWER MAGNETICS

DIVISION OF TRANSFACTOR INDUSTRIES INC.
65 Basaltic Rd. Concord, ON, L4K 1G4 Canada
Tel: 905-695-8844, 1-800-387-2840 Fax: 905-695-8855
www.RexPowerMagnetics.com

ENERGY EFFICIENT TRANSFORMER

- 3 Phase Isolation
- Dry Type
- ANN Self Cooled

Purchaser: TBA
PO#: TBA
SWO#: TBA
Qty: TBA

Coils: Aluminum
Cat. No.: BA75J-M/Z

kVA: 75
Primary: 600 Delta Volts
Secondary: 208 Y/120 Volts
Primary Taps: 2.5 %
-Taps FCAN 2
-Taps FCBN 2

Frequency: 60 Hz
Sound Level: 50 dB Max.
BIL: 10 kV
Insulation Class: 220° C
Temperature Rise: 150° C
Impedance: 4.0 - 5.0 %

Min. Efficiency: 98.0 %
- Calculated @ 35% Loaded

Weight: 515 Lbs

| Termination | Location | Lug Size |
|-------------|----------|-----------|
| Primary: | Front | 2-14 AWG |
| Secondary: | Front | 6-300 MCM |


Wiring Connection:

| Primary: | H1-H2-H3 | | |
|----------|----------|--|-------------|
| Voltage | % Tap | | Jumpers To: |
| 630 | 105.0 | | 1-1-1 |
| 615 | 102.5 | | 2-2-2 |
| 600 | 100.0 | | 3-3-3 |
| 585 | 97.5 | | 4-4-4 |
| 570 | 95.0 | | 5-5-5 |

| Secondary: | X0-X1-X2-X3 | | |
|------------|-------------|--|--|
| Voltage | Phase | | |
| 208 | 3 | | |
| 120 | 1 | | |

Connect Loads To:
X1-X2-X3
X0-X1, X0-X2,
and/or X0-X3

PRELIMINARY DRAWING ONLY
This drawing may NOT truly reflect our Final Design. Any resulting order(s) must be accompanied by, or refer to this drawing and be marked with any proposed changes.





Standards:

1. CSA Certified
- File No. LR34493
2. UL Listed
- File No. E108255

Standard Features:

1. Anti-vibration pads installed between the enclosure base and the core & coil assembly
2. Ground lug provided
3. Transformer meets Efficiency per CSA C802.2
4. Transformer meets NEMA TP-1 Efficiency Level



CSA Enclosure:

1. Type 3R (NEMA 3R)
- Sprinklerproof when the angle between sprinkler heads and opening in the enclosure does Not exceed 45 degree from the vertical.
2. Ventilated
3. ASA 61 grey
4. Floor/Wall mounting

| 2 | Updated Logo | AP | VS | May 13, 2011 |
|------|---------------------------|----|-------------|---------------|
| 1 | Updated Standard Features | SA | VS | Oct. 26, 2010 |
| REV# | Remarks | BY | Approved By | DATE |

Prepared by: SA
Approved by: VS
Date: OCT 26 2010