REX POWER MAGNETICS
DIVISION OF TRANSFACTOR INDUSTRIES INC.
65 Basaltic Rd. Concord, ON, L4K 1G4 Canada
Tel: 905-695-8844, 1-800-387-2840 Fax: 905-695-8855
www.RexPowerMagnetics.com

TRANSFORMER SPECIFICATION

- 3 Phase Auto
- Dry Type
- ANN -Self cooled

PRELIMINARY DRAWING ONLY
This drawing may NOT truly reflect our Final Design. Any resulting order(s) must be accompanied by, or refer to this drawing and be marked with any proposed changes.

Purchaser:	TBA
PO#:	TBA
SWO#:	TBA
Qty:	TBA

Coils:	Copper Wound
Cat. No.:	RC30J-H
kVA:	30
Primary:	600 Volts
Secondary:	480 Volts
Frequency:	60 Hz
Insulation Class:	220° C
Temperature Rise:	150° C
Impedance:	1.0 - 2.0 %
Weight:	115 Lbs

Termination	Location	Lug Size
Primary:	Front	Screws
Secondary:	Front	Screws

Wiring Connection:

Primary:

Voltage	Connect Lines To:
600	H1-H2-H3

Secondary:

Voltage	Connect Loads To:
480	X1-X2-X3

Standards:

1. CSA Certified
   - File No. LR34493
2. UL Listed
   - File No. E108255

Standard Features:

1. Anti-Vibration pads installed between the enclosure base and the core & coil assembly
2. Ground lug provided





FRONT VIEW



SIDE VIEW

CSA Enclosure:

- Type 1 (NEMA 1)
- Indoor Ventilated
- ASA 61 Grey
- Floor Mounting

Prepared by: AP
Approved by: VS
Date: DEC.4, 2008

X:\Drawings\NONC802\3P\AUTO\Auto Tranx Web\J-H\RC30J-H